


Specifications

Model	EMP-S3
Part Number	V11H179052
Projection System	Epson original 3LCD prism technology
Projection Method	Front / rear / ceiling mount
LCD	
Size	0.5" with MLA
Driving Method	Epson Poly-Silicon TFT LCD Active Matrix
Pixel Number	480,000 (800 x 600) pixels x 3
Native Resolution	SVGA
Aspect Ratio	4:3
Pixel Arrangement	Stripe
Projection Lens	
Type	Manual : Focus
F-number	1.4
Focal Length	16.6mm
Zoom Ratio (Digital)	1:1.35
Lamp	
Type	UHE 135W
Life (Typical)	2000 hours (High Brightness Mode) / 3000 hours (Low Brightness Mode)
Screen Size (Projected Distance)	30" to 300" diagonal (0.9 to 12.1m)
Keystone Correction	Vertical: +/- 30°
Brightness (Typical)	1600 ANSI Lumens (High Brightness Mode) / 1400 ANSI Lumens (Low Brightness Mode)
Contrast Ratio (Typical)	500:1
Brightness Uniformity (Typical)	85%
Color Reproduction	Full Color (16.7 million colors)
Speaker	1W Monoaural
Effective Scanning Frequency Range	
Pixel Clock	13.5 to 162 MHz
Horizontal	15 to 92 KHz
Vertical	50 to 85 Hz
Analog RGB Input / Output	
Display Performance	
Native	SVGA (800 x 600)
Resize	Up to SXGA (1280x1024)
Input Terminal	
Video	Mini D-Sub 15pin x 1
Audio	RCA (L / R) x 1 (Shared)
Output Terminal	
Video	Mini D-Sub 15pin x 1
Video Input / Output	
Display Performance	
Input Signal	550 TV Line NTSC, NTSC4.43, PAL, M-PAL, N-PAL, PAL60, SECAM SDTV / HDTV: 480i (525i), 480p (525p), 720p(750p), 1080i (1125i)
Input Terminal	
Component Video / Video RGB	Mini D-Sub 15pin x 1 (Shared)
S-Video	Mini DIN x 1
Composite Video	RCA x 1
Audio	RCA (L / R) x 1 (Shared)
Control Input / Output	
USB	USB Type B x 1
Operating Temperature	5°C to 35°C (41°F to 95°F)
Power Supply Voltage	100-240V +/- 10%, 50/60Hz AC
Maximum Dimension	327(W) x 246(D) x 98(H) mm
Weight	2.5 kg / 5.6 lbs
Fan Noise	28 dB (Low Brightness Mode)
Accessories	Power cord, Mini D-Sub 15-pin VGA cable, Remote Control (battery included), User's Manual CD-ROM, Setup Guide, Soft Carrying Bag

Connector Panel



Options & Accessories

ELPLP33 Replacement Lamp
Part No.: V13H010L33

ELPAF08 Air Filter Set
Part No.: V13H134A08

ELPKC19 Mini D-sub 15pin to
Component Video Conversion Cable (3 meters)
Part No.: V12H005C19

INDIA

Epson India Pvt Ltd
Tel: (91) 080-3051-5000 Fax: (91) 080-3051-5005
www.epson.co.in

INDONESIA

PT Epson Indonesia
Tel: (62) 021-572-3161 Fax: (62) 021-572-4357
www.epson.co.id

MALAYSIA

Epson Trading (M) Sdn Bhd
Tel: (60) 03-5628-8288 Fax: (60) 03-5628-8388
www.epson.com.my

PHILIPPINES

Epson Philippines Corporation
Tel: (63) 02-813-6567 Fax: (63) 02-811-1163
www.epson.com.ph

SINGAPORE

Epson Singapore Pte Ltd
Tel: (65) 6337-7911 Fax: (65) 6334-2716
www.epson.com.sg

THAILAND/INDO-CHINA

Epson (Thailand) Co., Ltd
Tel: (66) 02-670-0680 Fax: (66) 02-670-0688
www.epson.co.th

Projection Distance

Diagonal Screen Size (Inches)	Wide (cm)	Tele (cm)
30	87	119
40	117	159
60	177	240
80	237	321
100	279	402
150	447	605
200	597	807
300	897	1212

Dealer's Stamp:

All products and brand names herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All images are simulated in this brochure. Specifications are subject to change without prior notice.