

PRINTER TYPE

PRINTING METHOD Electrophotography + Laser
RESOLUTION 600dpi
PRINTING SPEED Mono 20ppm(A4 at 600dpi X 600dpi)
CPU 32bit RISC 48MHz

PAPER HANDLING

PAPER FEED METHOD
 Standard Paper Cassette (Universal)
Paper size: A4, A5, B5, LT, HLT, LGL, EXE, GLG, GLT, F4
Envelope: Mon, C10, DL, C5, C6, IB5
Transparencies: A4, LT
Label: A4, LT
Input Capacity: 150 sheets
Output Capacity: 100 sheets
Paper Thickness
Weight: 60 - 163 g/m²

INTERFACES

STANDARD IEEE1248 compatibility parallel interface
 USB 1.1 interface

MEMORY

2 MB

WARM-UP TIME

21 seconds or less (From power on)
 16 seconds or less (From Sleep mode)

FIRST PRINT TIME

Less than 13 seconds (Standard MP tray A4)

ACOUSTIC NOISE

SLEEP: 30dB
STAND BY: 39dB Ave.
DURING OPERATOR: 54dB Ave.

DURABILITY

5 years or 180,000 pages whichever comes first

MONTHLY PRINT VOLUME

MAXIMUM: 15,000 pages
AVERAGE: 2,500 pages

POWER REQUIREMENTS

POWER SUPPLY / FREQUENCY: 220V - 240V
POWER CONSUMPTION 220V - 240V **MAXIMUM:** 825 W
OPERATION: 357 Wh Ave.
STANDBY MODE: 48 Wh Ave.
SLEEP MODE: 8 Wh Ave.

ENVIRONMENTAL CONDITIONS (OPERATING)

TEMPERATURE: 10 to 35°C
HUMIDITY: 15 to 85% RH

DIMENSIONS

WIDTH X DEPTH X HEIGHT: 385 X 279 X 261mm
Weight: 6kg (excluding consumables)

PRINTER DRIVER/UTILITY

PRINTER DRIVER FOR: Microsoft® Windows® 95/98/ME/2000/ XP,
 Windows NT™ version 4.0,
 Mac™ OS 8.6 or later,
 Mac™ OS X 10.1.2 or later

EPSON STATUS MONITOR 3 FOR: Microsoft® Windows® 95/98/ ME/2000/XP,
 Windows NT™ version 4.0,
 Mac™ OS 8.6 or later,
 Mac™ OS X 10.1.2 or later
BAR CODE FONTS FOR: Microsoft® Windows® 95/98/ ME/2000/XP,
 Windows NT™ version 4.0

SYSTEM REQUIREMENTS

WINDOWS ENVIRONMENT

Minimum requirements
CPU: Pentium
Clock: 133MHz
Memory: 16 MB
Interface: IEEE 1284 Parallel
 Standard USB (optional USB board is not supported)
 *Windows 95 is not supported with USB
OS: Windows 95/98/Me/XP/2000/NT4.0

Recommended requirements

CPU: Pentium
Clock: 233 MHz
Memory: 64 MB
Interface: IEEE 1284 Parallel
 Standard USB (optional USB board is not supported)
 *Windows 95 is not supported with USB
OS: Windows 95/98/Me/XP/2000/NT4.0

MAC ENVIRONMENT

Minimum requirements
CPU: Power MacG3 with standard USB or iMac,iBook
Clock: 233 MHz
Memory: 32 MB
Interface: Standard USB (optional USB board is not supported)
OS: Mac OS 8.6 or 9.x or X 10.1.2

Recommended requirements

CPU: Power MacG3 with standard USB or iMac,iBook
Clock: 233 MHz
Memory: 64 MB
Interface: Standard USB (optional USB board is not supported)
OS: Mac OS 8.6 or 9.x or X 10.1.2

CONSUMABLES

Developer Cartridge **Lifespan:** 3,000 pages* C13S050167
Photoconductor Unit **Lifespan:** 20,000 pages* C13S051099

*1 Appropriate number of sheets under conditions of continuous printing on A4/letter size paper with 5 percent page coverage.

LASER PRINTER EPSON EPL-6200L



*EPSON ESC/P2 stands for EPSON standard code for printers. This second generation printer control language supports scalable fonts as well as enhanced graphics capability.

It also provides complete backwards compatibility with EPSON's ESC/P, the standard printer language for dot matrix printing.¹ EPSON is a registered trademark of SEIKO EPSON CORPORATION. EPSON ESC/P2 is a trademark of SEIKO EPSON CORPORATION. PostScript is a trademark of Adobe Systems Incorporated or its subsidiaries and may be registered in certain jurisdictions. All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights for those marks. Specifications are subject to change without notice.

Dealer's stamp

EPSON

For enquiries, contact your nearest EPSON sales representatives :

INDIA - (91) 80-532 1266-70, CALCUTTA - 287 1355/56, CHENNAI - 820 3941/42, MUMBAI - 825 7286, NEW DELHI - 644 7201/2/3
INDONESIA - (62) 21-572 3161 **MALAYSIA** - (60) 03-562-88288 **PHILIPPINES** - (632) 813-6567
SINGAPORE - (65) 6472 2822 **THAILAND/INDOCHINA** - (66) 2670 0680

www.epson.com.sg