

SPECIFICATIONS of IR-310 Series Intelligent Register

CPU	Celeron™ 366 / 433 MHz
Memory	2 DIMM slots (256 MB max.)
Storage	FDD (1.44/3.5" standard), 1 HDD (3.5" 25.4 mm <1.0"> max. high) or 2 HDD (2.5" 9.5 mm <0.4"> max. high) can be installed CompactFlash™ card slot can be installed
Slots	PCI x 2
I/O	SERIAL x 6 (Internal x 2, External x 4) w/5V & 12V power for external by jumper switches (Internal two for Printer / Customer display and Touch panel) K/B & Mouse port w/PS/2 type (1 connector located on right side) 24V Drawer port x 1 Parallel x 1 (does not support OCIA) USB port x 2 (1 ch located on rear panel, 1 ch located on right side) Ethernet x 1 (10 BASE-T / 100 BASE-TX), wake on LAN support
Video	CHIPS 69000, SDRAM 2 MB
Others	Keylock 7 positions Power connector For External TM printers (TM-H6000, T88, U200, U300, U325 series) Power switch Soft switch on front for power off by software, main switch on right side Power supply Built-in, 100-240V w/auto switch, 280VA
BIOS	APM / Plug & Play / DMI
OS	Option (MS-DOS®, Windows® 95, Windows® 98, Windows® 2000, Windows NT® Workstation 4.0)
Size	Base unit 252 (W) x 454.5 (D) x 287 (H) mm <9.9" x 17.9" x 11.3"> (including cable cover)
Printer Units	Thermal Printer 56 column thermal (80 mm paper roll) Dot Matrix Printer 42 column dot matrix Hybrid Printer Slip printer 42 column dot matrix Receipt printer 56 column thermal TM Printer Tray Tray for one station TM printers or for TM-H6000
LCD With Touch Panel	12.1" TFT color (800 x 600), Resistive touch panel (314 (W) x 254 (D) mm) 10.4" DSTN color (640 x 480), Resistive touch panel (277 (W) x 208 (D) mm) 10.4" DSTN color (800 x 600), Resistive touch panel (277 (W) x 208 (D) mm)
LCD Without Touch Panel	10.4" DSTN color (640 x 480) (277 (W) x 208 (D) mm)
Options	Customer Display VFD (20 x 2-line display or 256 x 64 dots graphic display), w/Standard Pole (125 mm <4.9">), w/Extended Pole (244 mm <9.6">), OPTION) MSR Unit ISO 1, 2 & 3 truck, Fixed to LCD or Keyboard unit, Communication via KB interface NVRAM Unit 32 KB SRAM with battery backup can be installed Sound Exclusive Sound board can be installed CD-ROM Drive 24X speed slim drive Keyboard POS 84-K/B, Programmable (277 (W) x 208 (D) mm <10.9" x 8.19">), 28-Key Keyboard Unit