

PRINTER TYPE

PRINTING METHOD	Electrophotography + Laser
RESOLUTION	600dpi
PRINTING SPEED	Mono 34ppm(A4 at 600dpi X 600dpi)
CPU	300MHz

PAPER HANDLING

PAPER FEED METHOD

Paper Cassette	
Capacity (Std):	550 sheets
Capacity (Max):	1800 sheets
Paper size:	A4, A5, B5, LT, HLT, LGL, EXE, GLG, GLT, F4
Envelope:	Mon, C10, DL, C5, C6, IB5
Transparencies:	A4, LT
Label:	A4, LT
Paper Eject / Capacity	
Face down:	(Maximum 500 sheets)
Face up:	(Maximum 70 sheets)
Paper Thickness	
Weight:	60 - 216 g/m ²

DUPLEX PRINTING

Option

INTERFACES

STANDARD	10BaseT/100Base Tx Ethernet IEEE1248 parallel USB 1.1 interface
OPTION	1 slot for Type B interface card

PRINTER CONTROL LANGUAGE

STANDARD	Adobe® Postscript® 3™, PCL6, LJ4, ESC/P2, FX, ESC/Page, IBM Mode(1239X), GL2
-----------------	--

MEMORY

64 MB (Expandable to 256MB)

WARM-UP TIME

25 seconds or less (From power on)
17 seconds or less (From low power mode)

FIRST PRINT TIME

Less than 8.7 seconds (Standard MP tray: A4)

ACOUSTIC NOISE

STAND BY:	27dB Ave.
DURING OPERATOR:	53.6dB Ave.

DURABILITY

5 years or 1,000,000 pages whichever comes first

MONTHLY PRINT VOLUME

MAXIMUM:	150,000 pages
AVERAGE:	10,000 pages

POWER REQUIREMENTS

POWER SUPPLY / FREQUENCY:	220V - 240V ±10%
POWER CONSUMPTION 220V - 240V	MAXIMUM: 959 W
	OPERATION: 538 Wh Ave.
	STANDBY MODE: 76 Wh Ave.
	SLEEP MODE: 10 Wh Ave.

ENVIRONMENTAL CONDITIONS (OPERATING)

TEMPERATURE:	5 to 35°C
HUMIDITY:	15 to 80% RH

DIMENSIONS

WIDTH X DEPTH X HEIGHT:	428 X 468 X 404mm
WEIGHT:	20.9kg (excluding consumables)

PRINTER DRIVER/UTILITY

PRINTER DRIVER FOR:	Microsoft® Windows® 95/98/ME/2000/XP, Windows NT™ version 4.0, Mac™ OS 8.6 or later, Mac™ OS X 10.1.2 or later
EPSON STATUS MONITOR 3 FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
EPSON FONT MANAGER FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
EPSON BAR CODE FONTS FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
EpsonNet WINASSIST FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
EpsonNet MACASSIST FOR:	Mac™ OS 8.6 or later, Mac™ OS X 10.1.3 or later
EpsonNet DIRECT PRINT FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
EpsonNet INTERNET PRINT FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0
EpsonNet NDSP GATEWAY FOR:	Microsoft® Windows® 95/98/ ME/2000/XP, Windows NT™ version 4.0/ Novell® Netware® 5.0/5.1/6.0

CONSUMABLES

Imaging Cartridge	Lifespan: 17,000 pages*1	C13S051111
Fuser Unit(220V-240V)	Lifespan: 200,000 pages*1	C13S053017

OPTIONS

550-Sheet Paper Cassette Unit A4	C12C802091
Hard Disk Drive	C12C824061
Stacker	C12C802111
Duplex Unit	C12C802101

*1 Approximate number of sheets under conditions of continuous printing on A4/letter size paper with 5 percent page coverage.

MONOCHROME LASER PRINTER EPSON EPL-N3000



EPSON ESC/P2 stands for EPSON standard code for printers. This second generation printer control language supports scalable fonts as well as enhanced graphics capability.

It also provides complete backwards compatibility with EPSON's ESC/P, the standard printer language for dot matrix printing. EPSON is a registered trademark of SEIKO EPSON CORPORATION. EPSON ESC/P2 is a trademark of SEIKO EPSON CORPORATION. PostScript is a trademark of Adobe Systems Incorporated or its subsidiaries and may be registered in certain jurisdictions. All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights for those marks. Specifications are subject to change without notice.*

EPSON

Dealer's stamp

For enquiries, contact your nearest EPSON sales representatives :

INDIA - (91) 80-532 1266-70, CALCUTTA - 287 1355/56, CHENNAI - 820 3941/42, MUMBAI - 825 7286, NEW DELHI - 644 7201/2/3
INDONESIA - (62) 21-572 3161 MALAYSIA - (60) 03-562-88288 PHILIPPINES - (632) 813-6567
SINGAPORE - (65) 6472 2822 THAILAND/INDOCHINA - (66) 2670 0680

www.epson.com.sg